

21.5" LED Touchscreen Monitor

Specifications	
Part Number	401272
Touch Technology & Capacity	PCAP (Projected Capacitive) – Multi-Touch
Touch Interfaces	USB and Serial
Diagonal Size	Diagonal, Active Matrix TFT LCD
Aspect Ratio	16:9
Active Area	476.064 mm (H) x 267.79 mm (V)
Max Resolution	1920 (H) x 1080 (V)
Pixel Pitch	0.2479 mm x 0.24795 mm
Other Supported Resolutions	640 x 480; 800 x 600; 1024 x 768; 1280 x 720; 1280 x 800; 1280 x 960; 1280 x 1024; 1360 x 768; 1366 x 768; 1440 x 900; 1680 x 1050; 1920x1080
Video Refresh rate	60 Hz
Video I/O Ports	HDMI; DVI-D; VGA
Viewing Angle	Horizontal: $\pm 89^\circ$; Vertical: $\pm 89^\circ$
Number of Colors	16.7M (RGB 6-bits +Hi-FRC)
Brightness Rating	Min: 240 nit; Typical: 300 nit
Color Temperatures	
Response Time	Typ: 14ms
Contrast Ratio	Typ: 1000:1
Power	24V DC Adapter; Monitor input connector: 2.5mm locking barrel; Monitor input voltage range: 24V DC; Adapter input voltage range: 100-240V
Power Consumption	Typ: 13W; Max: 17W
Monitor Dimension	523.4mm x 268.00mm x 60.5mm
Weight	
Operating Temperature	0°C - +50°C
Storage Temperature	-20°C - +60°C
Humidity Range	10% - 90% Relative Humidity
On Screen Display	Accessible with provided Goldfinger Remote, Controls: Power, Back, Left, Right, Menu, Overscan; Picture Mode, Contrast, Brightness, Color, Tint, Sharpness, Backlight, Color Temp, Aspect Ratio, Noise Reduction, Mirror, Clock, Off Time, On Time, Sleep Timer, OSD Language, OSD Duration, Languages: English, French, Italian, German, Spanish, Chinese, Japanese
Mounting Options	VESA 200mm x 200mm; VESA 100mm x 100mm; Pre-Defined Perimeter Mounting
Warranty	3 Year Standard
Regulatory Approvals	United States: UL
Impact Protection	
Touchscreen Glass Treatment	Chemically treated for strength*

Optional Peripherals

Peripherals							
	HDMI	DVI-D	VGA	Display Port	USB	Serial	LED Controller
P/N							